

Update Frequenzen

Technologieneutralität 900/1800 MHz

Dietmar Zlabinger

Mobilregulierungsdialog 28.03.2011



Novelle der Kommissionsentscheidung 900/1800 MHz

- Bisher: Entscheidung 2009/766/EG: GSM + UMTS
- **Novelle:**
 - zusätzlich LTE, WiMax
 - Zustimmung im RSCOM am 23. März 2011
 - Nationale Umsetzung bis 31. Dezember 2011
 - Veröffentlichung im Amtsblatt im Q2/2011 erwartet
- Details: http://www.rtr.at/de/tk/Spectrum_GSM_Refarm



ANNEX

List of terrestrial systems referred to in Article 3 and Article 4(2)

The following technical parameters shall be applied as an essential component of the conditions necessary to ensure coexistence in the absence of bilateral or multilateral agreements between neighbouring networks, without precluding less stringent technical parameters if agreed among the operators of such networks.

Text der Novelle

- Anhang wird ersetzt:

Systems	Technical parameters	Implementation deadlines
UMTS complying with UMTS Standards, as published by ETSI, in particular EN 301908-1, EN 301908-2, EN 301908-3 and EN 301908-11	<ol style="list-style-type: none">1. Carrier separation of 5 MHz or more between two neighbouring UMTS networks.2. Carrier separation of 2.8 MHz or more between a neighbouring UMTS network and a GSM network.	9 May 2010
LTE complying with LTE Standards, as published by ETSI, in particular EN 301908-1, EN 301908-13, EN 301908-14, and EN 301908-11	<ol style="list-style-type: none">1. A frequency separation of 200 kHz or more between the LTE channel edge and the GSM carrier's channel edge between a neighbouring LTE network and a GSM network.2. No frequency separation is required between LTE channel edge and the UMTS carrier's channel edge between a neighbouring LTE network and a UMTS network.3. No frequency separation is required between LTE channel edges between two neighbouring LTE networks.	31 December 2011
WiMAX complying with WiMAX Standards, as published by ETSI, in particular EN 301908-1, EN 301908-21 and EN 301908-22	<ol style="list-style-type: none">1. A frequency separation of 200 kHz or more between the WiMAX channel edge and the GSM carrier's channel edge between a neighbouring WiMAX network and a GSM network.2. No frequency separation is required between the WiMAX channel edge and the UMTS carrier's channel edge between a neighbouring WiMAX network and a UMTS network.3. No frequency separation is required between WiMAX channel edges between two neighbouring WiMAX networks.	31 December 2011



Dietmar Zlabinger

Kontakt:

RTR-GmbH (Rundfunk und Telekom Regulierungs-GmbH)

Mariahilfer Straße 77-79
1060 Wien
Austria

T: +43 1 58058 304
E: dietmar.zlabinger@rtr.at

<http://www.rtr.at/frequenzen>